




cutting




partial stripping



complete stripping



intermediate stripping



stripping in 2 stages

OUTER AND INNER CUTTING AND STRIPPING MACHINE	GM6S
Alimentation	Monophase 230 V 50/60 Hz
Pneumatic Alimentation	6 Bar
Absorbment	800 W
Outer Stripping Length	Front 10÷120 mm – Back 10÷120 mm
Inner Stripping Length	Front 1÷120 mm – Back 1÷80 mm (From 2 to 5 Poles)
Workable Sections	4÷30 mm ² / Diameter 3÷12,5 mm
Cutting Length	1 mm÷100 m
Feeding	4 Belt Feeding (16 Drive Motors)
Workable Cable	PVC-Teflon-Silicon-Glass
Productivity	L = 100 mm, 2.000 – 5.000 pcs/h
Tolerance	<= 0,002 xL (L=Cutting Length)
Display	Touch Screen LCD Liquid Cristal Display
Memory	99 Programs
Weight	120 Kg
Dimensions	700x500x600 mm (WxDxH)

Functions of the Outer and Inner Cutting and Stripping Machine GM6S

- Cut and strip single core cables up to 30 mm²
- Remove the outer sheath and strip the inner conductors of multiple cables up to 5 poles in a single step
- Ideal for high productions

